

# PRODUCT DATA SHEET

**Series 950i**  
Sliding Door  
5" Frame Depth

PERFORMANCE DATA <sup>1</sup>	OPERATION	AAMA RATING	TEST SIZE (inches)	AIR (cfm/ft <sup>2</sup> ) @ 6.24 psf	WATER (psf)	DESIGN PRESSURE (psf)	STRUCTURAL OVERLOAD (psf)	OITC	U-FACTOR (BTU/HR/FT <sup>2</sup> /F)
	Sliding	AW-PG75	123 x 95	0.13	12	75	112.5	Consult AWM	See Below

<sup>1</sup>Based on independent certified laboratory testing per AAMA/WDMA/CSA/101/I.S.2/A440. Field results will vary based on size, test methods, accessories & conditions

## STANDARD FEATURES

- Thermal strut thermal barrier for enhanced performance and dual finish capability
- Stainless steel covered raised track and adjustable ball bearing rollers provide smooth operation
- Heavy duty thumb-turn single-point stainless steel mortise lock and keeper
- Single slide design available in 2, 3 or 4-lite configurations
- Wet glazed with structural silicone for extreme seal strength and longevity

## OPTIONAL FEATURES

- Dual glazing with removable access panels (allows for vandal resistant polycarbonate glazing or 5/8" deep integral blinds)
- Exterior key locks
- 15 psf sill for increased water resistance
- Exterior applied or between the lites of dual glazing muntin grids
- Heavy duty rolling insect screens (fiberglass, aluminum or stainless steel mesh)
- Hurricane Windborne Debris Impact Resistance (Large Missile)



THERMAL PERFORMANCE CHART <sup>1</sup>	DOOR SIZE (XO)	CENTER OF INSULATED GLASS U-FACTOR/SPACER TYPE ("Alum."=Aluminum, "Warm"=Warm Edge) <sup>2</sup>							
		0.33/Alum.	0.33/Warm	0.29/Alum.	0.29/Warm	0.24/Alum.	0.24/Warm	0.20/Alum.	0.20/Warm
	79" x 79"*	0.486	0.475	0.458	0.447	0.425	0.413	0.383	0.372
96" x 96"	0.458	0.449	0.429	0.419	0.394	0.384	0.349	0.340	

<sup>1</sup>Based on independent certified simulations in accordance with NFRC 100

<sup>2</sup>Consult AWM for additional configurations

\*Designates NFRC Gateway size